

INVERTERS

SPF 6000 ES Plus

Off-grid inverter · Single-phase · 6 kW


6 kW

RATED POWER

Single-phase

PHASE

2

MPPT TRACKERS

93 %

MAX. EFFICIENCY

Parameter	Unit	SPF 6000 ES Plus
PV input		
Max. PV input power	W	8000
Max. PV input voltage	V	500
MPPT voltage range	V	120 – 450
Max. input current per MPPT	A	16
Number of MPPT trackers		2
PV strings per MPPT		1
Max. solar charge current	A	100
AC output		
Rated output power	W	6000
Max. apparent power	VA	6000
Rated AC voltage	V	230
AC voltage regulation (battery mode)	%	+/-5
Phase		Single-phase
Rated AC frequency	Hz	50/60
Surge power	VA	12000
Output waveform		Pure sine wave
Transfer time		10 ms typical; 20 ms max.
Max. parallel units		6
Number of AC input terminals		2 (with integrated transfer switch)
Max. AC charge current	A	80
AC input voltage	V	230
AC input selectable voltage range		170-280 VAC (for personal computers); 90-280 VAC (for home appliances)
AC input frequency range		50 Hz / 60 Hz (auto sensing)

Parameter	Unit	SPF 6000 ES Plus
Battery		
Battery type		Lithium / Lead-acid
Nominal battery voltage	V	48
Efficiency		
Max. efficiency	%	93
General data		
Dimensions (W x H x D)	mm	460 × 395 × 132
Weight	kg	13.5
Ingress protection (IP rating)		IP20
Operating temperature range	°C	0 – 55
Storage temperature	°C	–15 – 60
Relative humidity	%	5 – 95
Max. operating altitude	m	<2000

Specifications are subject to change without notice. Values are typical at 25 °C unless stated.
XUSION is a brand of Hunan New Lithium Aviation Technology Co., Ltd.

E-mail lidreamtec@163.com
WhatsApp +86 133 5280 0772